CJFR11

Abrasive	:	Silicon Carbide
Backing	:	J Flexible Poly-Cotton Cloth
Bond	:	Resin Over Resin
Coating	:	Closed
Grit Range	:	60-600
Features	:	Ideal for brass, copper, non ferrous steel, aluminium and zamak in narrow belts and rolls. J flexible poly-cotton cloth backing with Silicon Carbide abrasive. Flexible structure, ideal for armature, valve and relevant sectors.

					60	**80**	100	120	150	180	220	240	280	**320**	**400**		600				



Narrow Belt

Roll

Product Form

- Jumbo Roll
- Segmented Belt
- Wide Belt
- Narrow Belt
- Roll
- Sheet
- Disc
- Hook & Loop Disc
- Flap Wheel
- Flap Disc
- Fibre Disc
- Quick Lock Disc

Application Method

- Polishing
- Endless Belt
- Hand Use
- Wide Belt
- Mini Belt
- Flap Wheel Machine
- Floor Sanding
- Orbital Sander
- Hand Grinder
- Mini Disc Sander

Application Area

- Wood
- Low Alloy Steel
- Stainless Steel / Inox
- High Alloy Steel / Heat Resistant Steel
- Aluminium / Zamak
- Brass / Copper / Non Ferrous Metal
- Paint / Varnish / Lacquer
- Plastic / Rubber / Leather
- Cast Iron
- Glass / Stone / Granite / Ceramic

Features

- Antistatic Feature
- Suitable for Wet Applications
- Friction & Heat Absorbant
- Anti-Clogging
- Flexible for Curved Surfaces
- Easily Tearable by Hand
- Tear Resistant