Abrasive	Backing	Bond	Coating	Version	Abrasive	Backing	Bond	Coating	Version	Jumbo Width (mm)	Grit Range	Status																									
												16	24	36	40	50	60	80	100	120	150	180	220	240	280	320	400	500	600	800	1000	1200	1500	2000
A	H	R	3	1	AO	Polyester Film	Resin Over Resin	Stearat & Semi-Open	Std.	1380	40-2000				●		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
A	C	R	3	1	AO	C Weight Paper		Stearat & Open	Std.	1440	40-1200				○		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○			
A	F	R	7	1	AO	F Weight Paper		Antistatic & Closed	Std.	1650	40-600				●	●	●	●	●	●	●	●	●	●	●	●	●	●	●								
C	F	R	9	1	SC			Antistatic & Semi-Open	Std.	1650	40-800				●	●	●	●	●	●	●	●	●	●	●	●	●		●	●							
Z	F	R	9	1	ZR			Antistatic & Semi-Open	Std.	1650	36-400			○	●	●	●	●	●	●	●	●	●	●	●	●										
CE	F	R	9	1	CE			Antistatic & Semi-Open	Std.	1650	24-220		○	●	●	●	●	●	●	●	●	●	●													
A	J	R	1	1	AO	J Cotton Cloth		Closed	Std.	940	40-400				●	●	●	●	●	●	●	●	●	●	●	●										
A	J	R	1	2	AO			Closed	Ver.	1650	40-400				●	●	●	●	●	●	●	●	●	●	●	●										
A	JF	R	1	2	AO	J Flexible Cotton Cloth		Closed	Ver.	1650	60-600						●	●	●	●	●	●	●	●	●	●	●	●								
A	JF	R	1	1	AO			Topsize & Closed	Std.	1650	60-800						●	●	●	●	●	●	●	●	●	●	●	●	●							
A	JF	R	1	3	AO	J Flexible Poly-Cotton Cloth		Closed	Ver.	1650	80-600						●	○	●	●	●	●	○	●	●	●		●								
A	JF	R	1	0	AO			Topsize & Closed	Ver.	1650	60-600						●	●	●	●	●	●	●	●	●	●		●								
C	JF	R	1	1	SC			Closed	Std.	1650	60-600						●	●	○	○	○	○	○	○	○	●		●								
CE	F		5	1	CE			Topsize & Closed	Std.	1650	60-220						●	●	●	●	●	●	●													
A	XF	R	1	1	AO	X Semi Flexible Cotton Cloth		Closed	Std.	1650	40-600				●	○	●	●	○	○	○	○	○	○	○	○	○		○								
A	XF	R	1	2	AO			Closed	Ver.	1650	40-400				●		●	●	●	●	●	●	●	●	●	●										
A	X	OP	2	1	AO	X Cotton Cloth		Semi-Open	Std.	1650	16-400	○	○	●	●	○	●	●	●	●	●	●	○	●	○	●	○									
A	X	R	2	1	AO	X Poly-Cotton Cloth		Semi-Open	Std.	1650	36-400			○	○		○	○		○	○	○		○			○									
Z	X	R	1	1	ZR	X Heavy Cotton Cloth		Closed	Std.	1650	24-120		●	●	●	●	●	●	●	●																
Z	X	R	1	2	ZR			Closed	Ver.	1650	36-120			○	●		●	●	○	●															
A	XE	R	1	1	AO			Closed	Std.	1650	40-120				●		●	●		●															
A	XP	R	1	1	AO	X Heavy Poly-Cotton Cloth		Closed	Std.	1650	24-280		○	●	●		●	●	●	●	●	●	○	○	○										
Z	XP	R	1	1	ZR			Closed	Std.	1650	24-120		●	●	●	●	●	●	●	●															
Z	XP	R	2	2	ZR	Y Poly-Cotton Cloth		Closed	Ver.	1650	24-120		●	●	●	●	●	●	●	●															
CE	Y		5	1	CE			Topsize & Closed	Std.	1650	36-120			●	●	○	●	●		○														
A	YX	R	1	1	AO	YY Polyester Cloth		Closed	Std.	1650	16-600	○		○	○		●	●	●	●	●	●	●	○	●	●	○	○	○						
C	YX	R	1	1	SC			Closed	Std.	1650	16-320	○	○	●	○		○	●	●	●	○	○		○	○	○									
Z	YY	R	1	1	ZR			Closed	Std.	1650	24-400		●	●	●	●	●	●	●	●	○	○	○	○	○	○	○								
Z	YY	R	5	1	ZR			Topsize & Closed	Std.	1650	24-120		○	●	●	○	●	●	○	●															
CE	YY	R	2	1	CE			Semi-Open	Std.	1650	24-120		●	●	●	●	●	●	●	●															
CE	YY	R	5	1	CE			Topsize & Closed	Std.	1650	36-120			●	●	○	●	●	●	○															
CE	YY	R	5	2	CE			Topsize & Closed	Ver.	1650	24-120		○	●	●		○	●		○															
AG	YY	R	2	1	AG			Semi-Open	Std.	1650	80-600							●		●		●		●		●	●		●						
AG	YY	R	2	4	AG			Semi-Open	Ver.	1650	80-600							●		●		●		●		●	●		●						
C	Z	R	7	1	SC	Z Polyester Cloth		Antistatic & Closed	Std.	1650	36-220			○	●	●	●	●	●	●	●	●	○												
A	WE	R	1	1	AO	Vulcanized Fibre		Closed	Std.	1650	16-120	●	●	●	●	●	●	●	●	●															
A	W	R	1	1	AO			Closed	Std.	1650	16-400	●	●	●	●	●	●	●	●	●	○	○			○	○	○								
Z	W	R	1	1	ZR			Closed	Std.	1650	24-120		●	●	●		●	●	○	●															
Z	W	R	5	1	ZR			Topsize & Closed	Std.	1650	24-120		○	●	○	○	●	○		○															
CE		R	5	1	CE			Topsize & Closed	Std.	1650	24-120		●	●	○	○	●	●	○	●															

AO: Aluminum Oxide | SC: Silicon Carbide | ZR: Zirconia | CE: Ceramic | AG: Compact Aluminum Oxide | Ver.: Version | Std.: Standard | ●: Stock Item / Suitable | ○: Non-Stock Item

Product Forms													
Jumbo	Segmented Belt	Wide Belt	Narrow Belt	Roll	Sheet	Disc	Hook & Loop Disc	Flap Wheel	Flap Disc	Fibre Disc	Quick Lock Disc
●							●				
●							●				
●	●	●	●	●	●	●	●				
●	●	●	●	●	●	●	●				
●	●	●	●	●	●	●	●				
●	●	●	●	●	●	●	●				
●				●	●						
●				●	●						
●			●	●	●						
●			●	●	●						
●			●	●							
●			●	●							
●			●	●							
●			●	●							
●			●	●				●			
●			●	●				●			
●			●	●	●	●	●				
●		●	●	●	●	●	●				
●		●	●	●		●	●	●	●		
●			●	●		●	●	●	●		
●		●	●	●					●		
●		●	●	●					●		
●		●	●	●					●		
●			●	●					●		
●		●	●	●		●	●				●
●		●	●	●		●					
●		●	●	●		●	●				
●		●	●	●							●
●		●	●	●		●	●				
●		●	●	●							●
●		●	●	●		●	●				
●		●	●	●		●	●				
●	●	●									
●										●	
●										●	
●										●	
●										●	
●										●	

Application Method										
Polishing	Belt	Hand Use	Wide Belt	Mini Belt	Flap Wheel Machine	Floor Sanding	Orbital Sander	Hand Grinder	Mini Disc Sander
							●		
							●		
●	●	●	●			●	●		
	●	●	●			●	●		
	●	●	●			●	●		
	●	●	●			●	●		
●		●							
●		●							
●		●	●						
●		●	●						
●	●								
●	●								
●	●	●	●		●				
●	●	●	●		●				
	●	●		●		●	●		
	●	●	●	●		●			
	●				●	●	●	●	
	●				●	●	●	●	
	●							●	
	●			●		●		●	
	●			●				●	
	●			●		●		●	
	●			●				●	
	●		●	●		●	●		●
	●		●	●			●		
	●		●	●		●	●		
	●		●	●					●
	●		●	●		●	●		
	●		●	●					●
	●		●	●		●	●		
	●		●	●					
●	●		●				●		
●	●		●				●		
●	●		●				●		
●	●		●				●		
●	●		●				●		

Application Area										
Wood	Low Alloy Steel	Stainless Steel / Inox	High Alloy Steel / Heat Resistant Steel	Aluminium / Zamak	Brass / Copper / Non Ferrous Metals	Paint / Varnish / Lacquer	Plastic / Rubber / Leather	Cast Iron	Glass / Stone / Granite / Ceramic
	●	●				●			
●						●	●		
●	●	●							
●				●	●				●
●	●	●	●	●					
●	●	●	●	●					
●	●								
●	●			●	●		●	●	
●	●	●	●		●				
●	●	●	●				●		
●	●	●							
●	●	●					●		
●	●	●	●		●		●		
●		●	●		●			●	
●	●	●	●	●			●	●	
●		●	●		●			●	
●	●	●	●		●		●	●	
●	●	●	●					●	
●	●	●	●					●	
●	●	●	●					●	
●	●	●	●					●	
●	●	●	●	●				●	
●	●	●	●	●				●	
●	●	●	●					●	
●	●	●	●					●	
●	●	●	●					●	
●	●	●	●					●	
●	●	●	●					●	
●	●	●	●					●	
●	●	●	●					●	
●	●	●	●					●	
●	●	●	●					●	
●	●	●	●					●	
●	●	●	●					●	
●	●	●	●					●	

Features							
Antistatic Feature	Suitable for Wet Applications	Friction & Heat Absorbant	Anti-Clogging	Flexible for Curved Surfaces	Easily Tearable by Hand	Tear Resistant
	●		●			●
			●			
●						
●						
●						
●						
				●	●	
				●	●	
				●	●	
		●		●		
				●		
		●		●		
				●	●	
		●		●	●	
	●					●
	●					●
	●					●
	●	●				●
	●					●
	●	●				●
	●	●				●
●						●
						●
						●
						●
						●